



### 3) TSフランジ

円/枚

項目	形状						
	材質	PVC			HT		HI
呼び径A(B)	型式	10K	5K	上水用	10K	5K	10K
	13 (3/8)		450	430	-	1,030	1,030
15 (1/2)		460	450	-	1,160	1,060	650
20 (3/4)		530	510	-	1,400	1,330	740
25 (1)		790	670	-	2,040	1,750	1,090
32 (1 1/4)		1,020	810	-	2,730	2,180	1,420
40 (1 1/2)		1,030	980	-	2,890	2,600	1,450
50 (2)		1,380	1,240	-	3,710	3,430	1,910
65 (2 1/2)		1,750	1,560	-	5,030	-	2,450
75 (3)		-	-	3,110	-	-	-
80 (3)		2,150	1,910	-	6,850	-	3,030
100 (4)		3,050	2,760	4,100	9,300	-	4,270
125 (5)		3,710	3,610	5,320	11,880	-	5,180
150 (6)		5,980	5,170	7,880	17,750	-	8,370
200 (8)		7,960	7,550	10,910	30,990	-	11,260
250 (10)		11,130	10,230	15,330	47,050	-	15,590
300 (12)		13,660	-	18,450	62,670	-	19,130




### 4) 板フランジ

円/枚

項目	形状								
	材質	PVC						HI-PVC	HT
呼び径A(B)	型式	SP型		SB型		SJ型		SB型	SB型
		10K	5K	10K	5K	10K	5K	10K	10K
13 (3/8)		520	420	730	640	450	300	-	-
15 (1/2)		560	450	780	650	460	370	1,110	2,330
20 (3/4)		700	460	910	660	520	410	1,280	2,740
25 (1)		990	500	1,220	730	760	420	1,710	3,660
32 (1 1/4)		1,240	760	1,470	1,000	910	560	2,070	4,420
40 (1 1/2)		1,330	830	1,570	1,080	970	580	2,220	4,720
50 (2)		1,570	990	1,860	1,250	1,230	780	2,610	5,950
65 (2 1/2)		2,150	1,540	2,450	1,770	1,490	1,110	3,430	7,850
80 (3)		2,480	2,040	2,740	2,260	1,640	1,350	3,850	9,320
100 (4)		3,170	2,950	3,470	3,220	2,480	2,320	4,840	12,130
125 (5)		4,620	3,990	4,900	4,350	3,220	3,170	6,830	17,620
150 (6)		6,160	5,260	6,590	5,570	4,350	4,060	9,210	24,380
200 (8)		9,230	8,330	9,600	8,720	5,590	5,260	13,590	36,490
250 (10)		13,840	11,880	14,330	12,410	7,280	6,930	20,780	57,330

## 5) パッキン

円/枚

項目	EPDM			FKM	PTFE	IIR-X	トライガードPTFE		平面座用
	10K	5K	上水用	10K	10K	10K	10K	JPI150	10K
形状									
呼び径A(B)									
13 (3/8)	170	110	-	-	1,110	300	-	-	-
15 (1/2)	180	130	-	3,830	1,190	320	2,390	-	-
20 (3/4)	200	140	-	4,550	1,330	370	2,670	-	850
25 (1)	250	180	-	5,290	1,520	460	3,050	-	1,030
32 (1 1/4)	270	220	-	6,030	1,780	480	3,560	-	1,280
40 (1 1/2)	300	240	-	6,610	1,970	550	3,940	-	1,310
50 (2)	340	270	470	7,810	2,350	620	4,700	4,700	1,640
65 (2 1/2)	440	380	-	10,570	2,990	800	5,370	-	2,070
75 (3)	-	-	690	-	-	-	-	-	-
80 (3)	530	480	-	16,750	3,810	960	5,720	-	2,170
100 (4)	670	570	850	21,800	4,510	1,210	6,770	-	2,780
125 (5)	860	830	1,040	26,440	5,290	1,560	7,930	7,930	3,530
150 (6)	1,070	970	1,290	32,870	6,590	1,920	9,900	-	3,250
200 (8)	1,320	1,210	1,580	40,850	8,460	2,380	12,690	12,690	5,460
250 (10)	1,780	1,630	2,180	61,230	10,610	3,200	-	-	7,250
300 (12)	2,100	-	2,400	77,720	12,490	-	-	-	8,370
350 (14)	3,390	-	-	-	-	-	-	-	20,920
400 (16)	-	-	-	-	-	-	-	-	24,920

注) IIR-Xは、特別に開発されたIIRで耐塩素水性に優れています。


注) トライガードPTFEをエスロンPVDF配管の50A、125、200Aに使用する場合にはJPIクラスを選択ください。

## 6) ユニオン継手

円/個

項目	TS式				TS-バット式			
	PVC		HT		PVC/PVDF		HT/PVDF	
形状								
呼び径A(B)								
13 (3/8)	650	840	1,160	1,350	1,850	2,050	2,350	2,550
16 (1/2)	740	920	1,320	1,470	2,160	2,340	2,740	2,890
20 (3/4)	950	1,170	1,680	1,830	2,720	2,940	3,450	3,600
25 (1)	1,200	1,530	2,200	2,380	3,370	3,700	4,360	4,530
30 (1 1/4)	1,610	2,290	3,220	3,500	4,380	5,060	6,000	6,270
40 (1 1/2)	2,150	3,360	4,190	4,600	5,680	6,890	7,710	8,120
50 (2)	3,230	4,630	6,710	7,490	8,050	9,450	11,530	12,310
65 (2 1/2)	5,320	6,410	12,600	13,670	12,300	13,390	19,570	20,650
75 (3)	8,860	10,200	19,550	20,880	18,450	19,790	29,130	30,460
100 (4)	19,680	21,310	49,480	51,110	34,680	36,310	64,480	66,110

## 7) サドルバンド

呼び径A	PVC
形状	
本体材質	PVC
16	230
20	240
25	280
28	340
30	360
40	510
50	550
65	630
75	770
100	880
125	1,450
150	1,940
200	2,880